


PLUL1090
PLUL2090
Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.


Typology: WALL, CEILING

Ratings
- Built in LED module
- CCT 3000 K
- Wallward light (wall), downlight or uplight (ceiling)
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser




rosone standard /standard canopy





altezze disponibili
available heights



Product code composition

U-LIGHT / h10 cm or h25 cm ceiling lamp with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source	
PL	**UL 1 090 LED** (h10 cm)	**AN** anthracite grey	**XX** standard canopy	LED	63W - diffused beam **3000K** other CCT available on request. please ask to our customer service.
	UL 2 090 LED (h25 cm)	**RU** rust brown			

CE IP20 CRI90 dimmable 1-10V **LED** ~4904 lm 78 lm/W 100-240VAC

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).
Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code	PL	UL2090LED	AN	XX

Available colors



AN
Anthracite grey



RU
Rust brown

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER_____ NOTES_____

PLUL _ 090LED _ _ XX

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.